

12ft. Dump Height

The preferred balance of performance, reliability and capacity, the Stewart-Amos Sweeper Co.'s Starfire S-5t is a powerhouse for your most rigorous sweeping applications.

The S-5t is a full-size twin engine mechanical broom street sweeper mounted on a conventional or cab over commercial chassis and manufactured for a hard day of sweeping year-in and year-out.

Built with reliability and simplicity, the S-5t features a 5.0 cubic yard debris hopper and an in-cab controlled variable sweeping path for up to a 11 foot wide pass. Couple that with a 350 gallon water system and a 12' hopper dump height and you get the total package in street sweeping.

The benefits of the Starfire S-5t include:

- 5.0 Cubic Yard Hopper
- Quad (4) "X" Style Hopper Scissor Lift
- 4 Corner Hopper Lift
- Variable Height Dumping
- High Performance Sweeping
- Spring Balanced Brooms Auto Compensate for Wear
- Large Volume Dust Suppression
- Three Shaft Elevator Design
- Great Maneuverability and Mobility

- Rugged Construction
- Extremely Fuel Efficient
- Front & Rear Canopy Enclosures Maximize Component Protection
- Ease to Maintain
- Remarkably Quiet
- Safety Monitoring Camera SystemPM-10 Certified Rule 1186
- Proudly made in the U.S.A.



The Starfire series has built a reputation for rugged reliability and superior sweeping performance. Let us build one for you. Call your dealer today to arrange for a demonstration.

Stewart-Amos Sweeper Co.'s Starfire Sweeper Series - The Powerhouse in Broom Sweepers



Optional pressure washer system with extra long spray hose.


Exclusive 3-Shaft Elevator

BENEFITS:

LONGER LASTING. 3rd shaft ensures just the right amount of upper chain support and tension. Extends chains wear life and eliminates chain slappina.

REDUCED MAINTENANCE COSTS. 3rd shaft doubles amount of available chain adjustments. This and optimum upper chain support reduces chain wear and need to remove chain links by more than 50%.

BETTER LOADING PERFORMANCE. Maintains unrestricted debris movement. 3rd shaft maintains optimum chain spacing ensuring effective sweeping of large/bulky debris to minimize clogging.





Massive quad (4) "X" style lift scissors with four corner lift provide exceptional hopper stability especially when dumping wet, unbalanced or sticky debris.

S-5t SPECIFICA

Sweeping Path: 132 in. maximum* Debris Hopper: 5.0 cubic yards volumetric Dump Height (variable): 15" to 144"

Overall Length*: 23'4"
Overall Height*: 9' with std. strobes
GVWR*: 33,000#
*Based upon sweeper unit mounted on
Freightliner M2 conventional chassis

Main Broom: Length: 58" Diameter: 36" Type: Chevron strip broom

Drive: Hydraulic motor/direct drive and reversible Mounting: Full floating with in cab adjustable down

pressure, trailing arm design Lift Control: Hydraulic, in-cab Speed: Variable or constant Dirt Shoes: Carbide, 2" wide or Brush Style

Dual Gutter Brooms:Diameter: 42" or 54"
Type: Spring balanced, auto wear compensating Drive: Hydraulic and reversible Performance: Spring balanced with

auto-wear compensation Mounting: Free-floating, trailing arm Lift Control: Hydraulic, in-cab

Speed: Variable with auxiliary engine rpm Gutter Broom Tilt: in-cab (electric)

Dual float protected

Elevator System:Type: 10-flight squeegee with replaceable rubber

edging Liner: Bolt-in, 2 piece AR steel plates Chain: HD constant radius roller chain

Sprockets: Urethane Shafts: Three (see side bar above) Drive: Hydraulic, in-cab, and reversible

Lift Control: Hydraulic, in-cab Elevator Jam Warning: Light/Buzzer, in-cab Flushing System: Built-in

Debris Hopper:Volumetric Capacity: 5.0 cubic yards
Dump Height (variable): 15" to 144"
Dump angle: 56°
Hopper Door Reach from Side: 53" Inspection door, window, and safety prop 4 Corner hopper lift Quad (4) "X" style scissor lift

Hydraulic System - Twin Engine:
Pump: Dual tandem gear
Capacity: 24 gpm @ 2600 rpm
Reservoir: 45 gallons
Filter: 10 micron

Oil Cooler: Electric fan cooled & remote mounted Integral hydraulic pressure gauges

Twin Engine Sweeper Power: Make: Kubota V2403-M-T-E3

Interim Tier 4

Horsepower: 59 continuous @ 2700 rpm Type: in-line, four-cylinder turbo diesel Auto shutdown for high temperature/low pressure

Water Spray System: Tank Capacity: 350 gallons Construction: Non-Ferrous Mounting: Removable Pump: Electric diaphragm 3.6 GPM max.

Spray Nozzles:

4 on front spray bar
4 - two on each gutter broom
4 on main broom
Fill Hose: 2½" x 20' with NST coupler and inline strainer

4" Anti-siphon air gap Filter: 80 mesh

Elevator flush out system Air purge system and water drains

Electrical System:Alternator: 160 AMP Voltage: 12 volt

LED Lights: rear strobe lights; gutter brooms and rear mounted working lights; license plate; 2 stop/turn/tail; and clearance lights

Backup alarm

Camera and Monitor Safety System:
7" Color monitor with right side gutter broom and reverse color cameras

Instrumentation and Controls:

Sweeper function rocker switches (backlit) Elevator stall alarm Night light

Body: Standard white- high-gloss urethane enamel Undercarriage: Gloss black enamel

Standard Accessories:

Auto pickup in reverse Independent left and right gutter brooms
"ONE-TOUCH" Sweeping
Operators, parts and maintenance manuals
IN-CAB Adjustable gutter broom sweeping swath8ft. to 10ft. (Optional to 11ft.)

Limited Warranty Policy**
The Starfire S-5t sweeper is guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1,000 hours (whichever occurs first). Liability is limited to replacement of defect parts at factory or authorized dealer. The standard warranty of the chassis and auxiliary engine manufacturers apply.

Available Options: (not included in base price) *54" gutter brooms for an 11 foot swath Dual 3.6 GPM Water pumps for 7.2 GPM

Hopper vibrator Auto lube system

Pressure wash down system with 50' hose and wand

Arrow Board Strobe/Beacon Protector Front Mounted Magnet

Epoxy Hopper Liner Stainless Steel Hopper Extended Warranties

Body Paint Colors

High output twin engine 74.3 hp ILOS with S-5t

Others upon request
Wide variety of available chassis**
**Consult your dealer for details

• Please read actual warranty for details and limitations



Specifications are subject to change without notice